

Dry reciprocating sliding wear behaviour of alumina–silicon carbide nanocomposite fabricated by ceramic injection molding

Smirnov, Anton; Bartolome, Jose F.; Moya, J.S.; Kern, F.; Gadow, R. Journal of the European Ceramic Society 2011 / p. 469-474 : ill

Effect of basalt reinforcement type and content on the abrasive wear behaviour of polymer composites

Antonov, Maksim; Kers, Jaan; Liibert, Laura; Shuliak, Volodymyr; Smirnov, Anton; Bartolome, Jose F. Engineering materials and tribology : selected, peer reviewed papers from the 24th International Baltic Conference on Engineering Materials & Tribology (BALTMATTRIB & IFHTSE 2015), November 5-6, 2015, Tallinn, Estonia 2016 / p. 181-188 : ill

<https://doi.org/10.4028/www.scientific.net/KEM.674.181> [Conference Proceedings at Scopus](#) [Article at Scopus](#)

Electroconductive alumina-TiC-Ni nanocomposites obtained by spark plasma sintering

Rodriguez-Suarez, T.; Bartolome, Jose F.; **Smirnov, Anton**; Lopez-Esteban, S.; Diaz, L.A.; Torrecillas, R.; Moya, J.S. Ceramics international 2011 / p. 1631-1636 : ill

Sliding wear behaviour of alumina/nickel nanocomposites processed by a conventional sintering route

Rodriguez-Suarez, T.; Bartolome, Jose F.; **Smirnov, Anton**; Lopez-Esteban, S.; Torrecillas, R.; Moya, J.S. Journal of the European Ceramic Society 2011 / p. 1389-1395 : ill