

A mathematical model for abrasive erosion wear in composite Fe-based matrix with WC-Co reinforcement

Casesnoves, Francisco; Surženkov, Andrei Materials and contact characterisation VIII 2017 / p. 99-111 : ill

<http://dx.doi.org/10.2495/MC170101>

Nanoscale and microscale simulations of N-N junction heterostructures of 3C-4H silicon carbide

Rashid, Muhammad Haroon; Koel, Ants; Rang, Toomas; Gähwiler, Reto; Grosberg, Martin; Jõemaa, Rauno Materials and contact characterisation VIII 2017 / p. 235-248 : ill <http://dx.doi.org/10.2495/MC170241>

Non-destructive eddy current measurements for silicon carbide heterostructure analysis

Sahakyan, Armen; Koel, Ants; Rang, Toomas Materials and contact characterisation VIII 2017 / p. 49-60 : ill

<http://dx.doi.org/10.2495/MC170061>

The dependence of reverse recovery time on barrier capacitance and series on-resistance in Schottky diodes

Veher, Oleksandr; Sleptšuk, Natalja; Toompuu, Jana; Korolkov, Oleg; Rang, Toomas Materials and contact characterisation

VIII 2017 / p. 15-22 : ill <http://dx.doi.org/10.2495/MC170021>