

**Influence of A-Site Deficiency and Ca Concentration on the Electrical and Crystallographic Properties of (Nd<sub>0.2</sub>Sr<sub>0.7-x</sub>Ca<sub>x</sub>)Ti<sub>0.95</sub>Fe<sub>0.05</sub>O<sub>3-δ</sub>-Based Fuel Electrode for Solid Oxide Cells**

Paydar, Sara; Kooser, Kuno; **Volobujeva, Olga**; Granroth, Sari; Nurk, Gunnar ACS Applied Energy Materials 2024 / p. 5745 - 5754  
<https://doi.org/10.1021/acsaem.4c00824> [Journal metrics at Scopus](#) [Article at Scopus](#) [Journal metrics at WOS](#) [Article at WOS](#)

**Optimization of La<sub>0.2</sub>Sr<sub>0.7-x</sub>Ca<sub>x</sub>Ti<sub>0.95</sub>Fe<sub>0.05</sub>O<sub>3-δ</sub> fuel electrode stoichiometry for solid oxide fuel-cell application**

Paydar, Sara; Kooser, Kuno; Möller, Priit; **Volobujeva, Olga**; Granroth, Sari; Lust, Enn; Nurk, Gunnar ACS Applied Energy Materials 2022 / p. 10119 - 10129 <https://doi.org/10.1021/acsaem.2c01808> [Journal metrics at Scopus](#) [Article at Scopus](#) [Journal metrics at WOS](#) [Article at WOS](#)