

Dry reciprocating sliding wear behaviour of alumina–silicon carbide nanocomposite fabricated by ceramic injection molding

Smirnov, Anton; Bartolome, Jose F.; Moya, J.S.; Kern, F.; Gadow, R. Journal of the European Ceramic Society 2011 / p. 469-474 : ill

Industrial sustainable fabrication, SEM characterization, mechanical testing, ANOVA analysis of PP-PETF recycled composites : artificial intelligence and deep learning studies for nuclear shielding applications

Hussain, Abrar; Goljandin, Dmitri; Podgurski, Vitali; Yörük, Can Rüstü; Sergejev, Fjodor; Kübarsepp, Jakob; Maurya, Himanshu Singh; Rahmani Ahranjani, Ramin European polymer journal 2024 / art. 113082

<https://doi.org/10.1016/j.eurpolymj.2024.113082> [Journal metrics at Scopus](#) [Article at Scopus](#) [Journal metrics at WOS](#) [Article at WOS](#)

Physical–mechanical properties and morphology of filled low-density polypropylene: comparative study on calcium carbonate with oil shale and coal ashes

Krasnou, Illia; Nadeem, Faisal; Gregor, Andre; Yörük, Can Rüstü; Krumme, Andres Journal of Vinyl and Additive Technology 2022 / p. 94-103 : ill <https://doi.org/10.1002/vnl.21869> [Journal metrics at Scopus](#) [Article at Scopus](#) [Journal metrics at WOS](#) [Article at WOS](#)